



Accessories







Manual Reset Latching Device



Description

A spring-loaded, manual reset latching device, applicable for service on deluge and pre-action valve trims. In the "Ready" position, the DMR prevents draining of the deluge valve's control chamber, keeping the deluge valve closed. Once the deluge valve is actuated, the DMR shifts to its "Latched-Open" position, allowing draining of the control chamber and latching open the deluge valve. Manual resetting is accomplished by holding the DMR's knob until the deluge valve has closed.



Certification & Compliance


UL Listed (when installed on OCV control valves)





Features & Benefits

- Available in Brass (Standard) & Stainless Steel 316
- Simple design & maximal dependability
- Tough & durable construction



Operation

General			
Pressure Rating		25 bar / 360psi	
Fluid Temperature		80°C max / 175°F max	
Weight		0.91 kg / 2 lbs	
Materials	Standard		Optional*
Body & Bonnet	Brass		Stainless Steel
Stem	Stainless Steel		
Spring	Stainless Steel		
Ball	Viton®		
Elastomers	NBR		
Dimensions			
H (Height) max	102 mm / 4"		
W (Width)	77 ³ / ₁₀ " mm / 3"		
Port	Size		Connection
I	1/2" NPT		Priming Line
С	1/2" NPT		Control Chamber Actuating Device
V			Exhaust

^{*}Other materials available upon request. Minimum quantities may apply.

