




Model 127-3LF



Pressure Reducing Valves



General representation



Waterworks

Pressure Reducing Valve

Description

OCV 127-3LF, a pressure reducing valve with low-flow bypass, shall function to reduce a higher upstream pressure to a constant, lower downstream pressure regardless of fluctuations in supply or demand. The valve is applicable anywhere a pressure must be reduced to a manageable level under a wide range of demand that cannot normally be provided by a single valve.

Features & Benefits

- Combination of bypass regulator and pilot-operated main valve delivers widest possible flow range
- Reduces a higher inlet pressure to a lower outlet pressure
- Constant outlet pressure over wide flow range
- Pilot-operated main valve not subject to pressure fall off
- Outlet pressure is adjustable with single screw
- Isolation ball valves to facilitate maintenance & troubleshooting
- Adjustable opening/response speed
- Can be maintained without removal from the line
- Factory tested and can be preset to your requirements

Typical Applications

Irrigation Systems

Municipal Distribution Systems

Pump Systems



Industrial Plants

Hotels/Condominiums

Hospitals



Certification & Compliance

UL Water Quality / NSF 61-G & 372

NSF-ISO Quality System (9001)

American-Made: American Recovery & Reinvestment

Factory Mutual Approved

ABS Type Approval

CE (Conformité Européenne) Compliance




Operation

The bypass regulator, typically set 5-10 psi higher than the main valve pilot, controls the pressure under low flow conditions while the main valve remains closed. When the flow capacity of the regulator is exceeded, the pressure drops to the set point of the main valve pilot, causing the main valve to open and provide the higher flow. Response of the main valve is adjusted by an opening speed control.

Components

The OCV 127-3LF consists of the following components, arranged as shown on the schematic diagram:

- 1 OCV S65 Basic Control Valve
- 2 OCV 1340 Pressure Reducing Pilot
- 3 OCV 134C Bypass Regulator
- 4 OCV 126 Ejector - Fixed orifice pilot system supply restrictor
- 5 OCV 141-3* Flow Control Valve (Opening Speed Control)
*Note: OCV 141-2 Needle Valve used on sizes 1-1/4"-3"
- 6 OCV 159 Y-Type Strainer - Protects pilot system from dirt/debris
- 7 OCV 141-4 Isolation Ball Valves
- 8 OCV 155 Visual Indicator (Optional)



Pressure Table

End Connections	Ductile Iron	Steel/SST	Low-Lead Bronze
Standard (Maximum Working Pressures at 100°F)			
Threaded	640 psi	640 psi	500 psi
Grooved	300 psi	300 psi	300 psi
150# Flanged	250 psi	285 psi	225 psi
300# Flanged	640 psi	740 psi	500 psi

Based on ANSI flange ratings.

Flow Characteristics

$DP = sg (Q/C_v \text{ or } K_v)^2$ where: Q = Flow rate in USGPM (Standard) or Q = Flow rate in cubic meters/sec (Metric)
 C_v = Flow rate in USGPM @ 1 psi pressure drop (Standard) or
 K_v = Flow rate in cubic meters/sec @ 1 bar pressure drop (Metric)
 DP = Pressure drop in psi (Standard) or DP = Pressure drop in bar (Metric)
 sg = Specific gravity of line fluid

Standard		
Valve Size	Globe C_v	Angle C_v
1 1/4"	23	30
1 1/2"	27	35
2"	47	65
2 1/2"	68	87
3"	120	160
4"	200	270
6"	450	550
8"	760	1000
10"	1250	1600
12"	1940	2400
14"	2200	--
16"	2850	4000
24"	6900	--

Metric		
Valve Size	Globe K_v	Angle K_v
DN35	20	26
DN40	23	30
DN50	40 1/2	56
DN65	59	75
DN80	104	138 1/2
DN100	173	233 1/2
DN150	389	476
DN200	657 1/2	865
DN250	299	1384
DN300	1081	2076
DN350	1903	--
DN400	2465	3460
DN600	5968 1/2	--

Resetting, maintenance and periodic testing instructions must be followed as described in detail in the applicable OCV IOM (Installation, Operation & Maintenance) Manual.

Typical Materials

Part	Standard Material	Optional
Valve Body/Bonnet	Ductile Iron	Cast Steel, Stainless Steel, Aluminum
Seat Ring	Stainless Steel	Stainless Steel
Seat Retainer/Diaphragm Plate	Stainless Steel (up to 8"); Ductile Iron (10" & up)	--
Stem	Stainless Steel	Monel
Spring	Stainless Steel	--
Diaphragm	EPDM	Buna-N
Seat Disc	EPDM	Buna-N
Pilot	Stainless Steel	Stainless Steel
Tubing & Fittings	Stainless Steel	Stainless Steel

*Consult Factory for additional available materials.

Pressure Reducing Valves


General Arrangement & Dimensions

Standard Sizes													
DIM	End Connections	1 1/2"	2"	2 1/2"	3"	4"	6"	8"	10"	12"	14"	16"	24"
A	Threaded	8 3/4	9 7/8	10 1/2	13	--	--	--	--	--	--	--	--
	Grooved	8 3/4	9 7/8	10 1/2	13	15 1/4	20	--	--	--	--	--	--
	150# Flanged	8 1/2	9 3/8	10 1/2	12	15	17 3/4	25 3/8	29 3/4	34	39	40 3/8	62
	300# Flanged	8 3/4	9 7/8	11 1/8	12 3/4	15 5/8	18 5/8	26 3/8	31 1/8	35 1/2	40 1/2	42	62 3/4
B	Threaded	1 7/16	1 11/16	1 7/8	2 1/4	--	--	--	--	--	--	--	--
	Grooved	1*	1 3/16	1 7/16	1 3/4	2 1/4	--	--	--	--	--	--	--
	150# Flanged	2 5/16 - 2 1/2	3	3 1/2	3 3/4	4 1/2	5 1/2	6 3/4	8	9 1/2	10 5/8	11 3/4	16
	300# Flanged	2 5/8 - 3 1/16	3 1/4	3 3/4	4 1/8	5	6 1/4	7 1/2	8 3/4	10 1/4	11 1/2	12 3/4	18
C	Threaded	4 3/8	4 3/4	6	6 1/2	--	--	--	--	--	--	--	--
	Grooved	4 3/8*	4 3/4	6	6 1/2	7 5/8	--	--	--	--	--	--	--
	150# Flanged	4 1/4	4 3/4	6	6	7 1/2	10	12 11/16	14 7/8	17	--	20 13/16	--
	300# Flanged	4 3/8	5	6 3/8	6 3/8	7 3/16	10 1/2	13 3/16	15 9/16	17 3/4	--	21 5/8	--
D	Threaded	3 1/8	3 7/8	4	4 1/2	--	--	--	--	--	--	--	--
	Grooved	3 1/8*	3 7/8	4	4 1/2	5 5/8	--	--	--	--	--	--	--
	150# Flanged	3	3 7/8	4	4	5 1/2	6	8	11 3/8	11	--	15 11/16	--
	300# Flanged	3 1/8	4 1/8	4 3/8	4 3/8	5 13/16	6 1/2	8 1/2	12 1/16	11 3/4	--	16 1/2	--
E	All	6	6	7	6 1/2	8	10	11 7/8	15 3/8	17	18	19	27
F	All	3 7/8	3 7/8	3 7/8	3 7/8	3 7/8	3 7/8	6 3/8	6 3/8	6 3/8	6 3/8	6 3/8	8
G	All	6	6 3/4	7 11/16	8 3/4	11 3/4	14	21	24 1/2	28	31 1/4	34 1/2	52
H	All	10	11	11	11	12	13	14	17	18	20	20	28 1/2

Approximate Dimensions. *Grooved end not available in 1/4"

Metric Sizes													
DIM	End Connections	DN40	DN50	DN65	DN80	DN100	DN150	DN200	DN250	DN300	DN350	DN400	DN600
A	Threaded	222	251	267	330	--	--	--	--	--	--	--	--
	Grooved	222	251	267	330	387	508	--	--	--	--	--	--
	150# Flanged	216	238	267	305	381	451	645	756	864	991	1026	1575
	300# Flanged	222	251	283	324	397	437	670	791	902	1029	1067	1619
B	Threaded	37	43	48	57	--	--	--	--	--	--	--	--
	Grooved	25*	30	37	44	57	--	--	--	--	--	--	--
	150# Flanged	59-64	76	89	95	114	140	171	203	241	270	298	406
	300# Flanged	67-78	83	95	105	127	159	191	222	260	292	324	457
C	Threaded	111	121	152	165	--	--	--	--	--	--	--	--
	Grooved	111*	121	152	165	194	--	--	--	--	--	--	--
	150# Flanged	108	121	152	152	191	254	322	378	432	--	529	--
	300# Flanged	111	127	162	162	198	267	335	395	451	--	549	--
D	Threaded	79	98	114	114	--	--	--	--	--	--	--	--
	Grooved	79*	98	114	114	143	--	--	--	--	--	--	--
	150# Flanged	76	98	102	102	140	152	203	289	279	--	398	--
	300# Flanged	79	105	111	111	148	165	216	306	298	--	419	--
E	All	152	152	178	165	203	254	302	391	432	457	483	686
F	All	98	98	98	98	98	98	162	162	162	162	162	203
G	All	152	171	222	222	298	356	533	711	794	794	876	1321
H	All	254	279	279	279	305	330	356	457	508	508	508	724

Approximate Dimensions. *Grooved end not available in 1/4"



Technical Data

Temperature (Elastomers)	
Water	up to 110°C / 230°F max
Sizes	
Globe	1 1/4" - 24" / 32-600mm
Angle	1 1/4" - 16" / 32-400mm
Pressure Rating (Ductile Iron at 100°F/37.8°C)	
250 psi for ASME Class 150# & 640 psi for Class 300#	
End Connections	
Flanged	ISO-PN16 & ISO-PN25
	ASME/ANSI B16.42 & B16.5 Class 150# & 300#
	Additional options available upon request
Threaded	BSP/NPT
Grooved	ASME/ANSI AWWA 606
Elastomers	
EPDM	Buna-N
Coating Material	
NSF 61 Epoxy Coating	High Built, Fusion Bonded Apoxy
Main Valve Trim Material	
Stainless Steel	

Body & Cover Material	
Ductile Iron ASTM A536	Stainless Steel ASTM CF8M
Cast Steel ASTM A216	Aluminum
Trim Material	
Stainless Steel	
Optional Components	
Pressure Switch	Open/Close Speed Control
Limit Switch	Pressure Gauges
Drain Plug	Visual Position Indicator
Items to Specify	
Electrical features other than standard (24VDC, IP65/NEMA4)	
If explosion proof accessories are required such as solenoids, pressure switches, etc., please define classification	
Control trim material other than standard	
Required standards, certifications and approvals	

Engineering Specifications

The pressure reducing valve with low-flow bypass shall be a single-seated, line pressure operated, diaphragm actuated, pilot controlled valve. The valve shall seal by means of a corrosion-resistant seat and a resilient, rectangular seat disc. These, and other parts, shall be replaceable without removing the valve from the line. The stem of the main valve shall be guided top and bottom by integral bushings. Alignment of the body, bonnet and diaphragm assembly shall be by precision dowel pins. The diaphragm shall not be used as a seating surface, nor shall the pistons be used as an operating means. The pilot system shall be furnished complete and installed on the main valve. It shall include an opening speed control, Y-Type strainer, and isolation ball valves. The pressure reducing valve with low-flow

bypass shall be operationally and hydrostatically tested prior to shipment. The main valve body and bonnet shall be ductile iron. All ferrous surfaces shall be coated with 4 mils of epoxy. Elastomers (diaphragms, resilient seats and o-rings) shall be EPDM. The control pilots, opening speed control, isolation ball valves, and control line tubing shall be stainless steel. The pressure reducing valve with low-flow bypass shall be suitable for reducing inlet pressures of <X to X> psi to a constant outlet pressure of <X> psi at flow rates ranging from <X to X> gpm. The pressure reducing valve with low-flow bypass shall be an OCV 127-3LF, as manufactured by OCV, Tulsa, OK, USA.